

ODYSSEY Approved 12V Charger Listing

Supplier	Model	Amps	Battery Size	Telephone	Website
	TMAX-6A-1B	6	7-16 Ah	DISCONTINUED	
	OMAX-12A-1B	12	7-27 Ah		
	TMAX-12A-1B	12	7-27 Ah		
	OMAX-25A-1B	25	7-65 Ah		
	OMAX-40AS-3B	40	7-92 Ah		
	OMAX-50A-1B	50	7-114 Ah		
	OBC-6A	6	8-16 Ah	ODYSSEY Dealer Locator	ODYSSEY Battery Chargers
	OBC-12A	12	8-28 Ah		
	OBC-20A	20	8-55 Ah		

ODYSSEY Approved 12V "Trickle" Charger Listing (NOT for deep discharge cyclic applications)

Supplier	Model	Amps	Battery Size	Telephone	Website
ACI	1206CC 60CC-Rev C	3	7-16 Ah	905-565-0360	www.acichargers.com
Battery Minder	Model 2012-AGM Rev A	2	7-16 Ah	800-379-5579 x 208	www.batteryminders.com
DPI	1-12B990H10-Rev 14	0.9	7-27 Ah	800-334-5091	www.dpipower.com

ODYSSEY Approved 12V Charger Listing

Supplier	Model	Amps	Battery Size	Telephone	Website
Schauer	CM6A (replaces SW121060)	1/4/6	7-65 Ah	513-791-3030 x 13	www.battery-chargers.com
	CM12 (replaces SW121160)	1/8/12	7-114 Ah		
BatteryMinder	128CEC1 series (12v)	2/4/8	7-27 Ah	800-379-5579 x 208	www.batteryminders.com
	244CEC1 series (24v)	2/4/8	7-27 Ah		
	12248-AA-S3 Rev A	8	7-27 Ah		
CTEK Snowflake	MUS 7002 - with Alligator and eyelet connectors	7	7-16 Ah	North America 330-963-0981	www.ctek.com
	MUS 25000	25	27-65Ah		
Enerwatt- Use 8 Amp Setting	EWC12-248 Rev A	2	7-27 Ah	450-348-2370	www.batteriesexpert.com
		4			
		8			
Pro Charging Systems Dual Pro	Eagle Series i1225	25	27-65Ah	866-755-8399	www.prochargingystems.com
Interacter Needs Odyssey Chip	PS 1205 ODY	5	7 Ah	203-949-0199	www.interacter.com
	PS 1210 ODY	10	7-27 Ah		
	I/C/S 1225 ODY	25	7-65 Ah		

ODYSSEY Approved 12V Commercial Chargers (not intended for long term maintenance)

Supplier	Model	Amps	Battery Size	Telephone	Website
AutoMeter	BUSPRO 660	5A x 6	27-92 Ah	866-248-6356	www.autometer.com
Purkey / Clore	PAC-100	100	50-114 Ah	800-219-1269	www.purkeys.net/pac

ODYSSEY Approved 12V Marine Chargers

Supplier	Model	Amps	Battery Size	Telephone	Website
Powermania	Turbo M Series	6 - 30	7-114 Ah	888-581-8168	www.powermaniausa.com
Pro Charging Systems/Dual Pro - Professional Series DeltaVolt & Sportsman Series DeltaVolt chargers	PS 1 Delta Volt	15 - 1B	7-114 Ah	Sales Support 866-755-8399	www.prochargingystems.com
	PS 2 Delta Volt	15 - 2B	7-114 Ah		
	PS 3 Delta Volt	15 - 3B	7-114 Ah		
	PS 4 Delta Volt	15 - 4B	7-114 Ah		
	SS 1 Delta Volt	10 - 1B	7-114 Ah	Tech Support 800-742-2740	
	SS 2 Delta Volt	10 - 2B	7-114 Ah		
	SS 3 Delta Volt	10 - 3B	7-114 Ah		
	SS 4 Delta Volt	10 - 4B	7-114 Ah		
Promariner - Set to AGM Profile 2	ProNautic 3 Bank Rev. D 1215P-1220P-1230P-1240P 1250P & 1260P	15, 20, 30, 40, 50, 60	7-114 Ah	603-433-4440	www.promariner.com
Xantrex - Only for light cycling applications < 40% DOD	804-1220	20	7-114 Ah	574-522-9670	www.xantrex.com
Minnkota - Only available with eyelet connectors. Larger batteries will take more time to recharge	MK106PC - 1831060 (1 Bank x 6 Amp)	6	7-114 Ah	1-800-227-6433	www.minnkotamotors.com
	MK212PC - 1832120 (2 Bank x 6 Amp)	6	7-114 Ah		
	MK318PC - 1833180 (3 Bank x 6 Amp)	6	7-114 Ah		
	MK110PC - 1831100 (1 Bank x 10 Amp)	10	7-114 Ah		
	MK220PC - 1832200 (2 Bank x 10 Amp)	10	7-114 Ah		
	MK330PC - 1833300 (3 Bank x 10 Amp)	10	7-114 Ah		
	MK440PC - 1834400 (4 Bank x 10 Amp)	10	7-114 Ah		

Battery Cycling (Definition) - In situations where one is not quite sure whether the application is cyclic or standby (float), the following criteria may be used to determine the application category: If the average time on charge between two successive discharges is thirty (30) days, the application may be considered to be of a standby (float) nature. The minimum time between two successive discharges must not be less than fourteen (14) days. If either of these two criteria is not satisfied, the application should be considered cyclic.

EnerSys approval of chargers on this list is based on an evaluation of conformance with minimum general requirements at the time of testing. Charger requirements for specific applications vary based on factors such as frequency of discharge, depth of discharge, temperature and the time of recharge. The chargers listed are provided by 3rd parties and outside of EnerSys' control. EnerSys is not responsible for the reliability of the chargers or for any changes made by charger manufacturers which may make them inappropriate for use. EnerSys provides a series of chargers specifically designed for ODYSSEY products and encourages their use for maximum life, performance and reliability.