

COLD-CRANKING POWER WHEN YOU NEED IT

**ODYSSEY**<sup>®</sup>  
BATTERY

# The battery with the guts for genset demands

Genset batteries must provide big power and long service life. Thanks to Thin Plate Pure Lead (TPPL) technology, ODYSSEY<sup>®</sup> Extreme Series<sup>™</sup> and Performance Series<sup>™</sup> batteries deliver both, plus recharging capabilities that no conventional lead acid battery can match. ODYSSEY<sup>®</sup> batteries provide:

- Cold-cranking, high power density – ODYSSEY batteries can start and support a 400A load for >60 seconds, and a 500A load for 34 seconds
- Extended service life – 8 to 10 years, even with periodic high-rate discharges
- Quick recharge capabilities – ODYSSEY batteries can reach 90% State of Charge (SOC) in 2 hours
- Two-year storage life at room temperature without a boost charge

For more about how ODYSSEY batteries can handle genset applications, contact your ODYSSEY battery representative today.






[www.odysseybattery.com](http://www.odysseybattery.com)



Powered by **EnerSys**<sup>®</sup>  
Power/Full Solutions

## ODYSSEY® Extreme Series™ battery

Battery Type	Voltage	Pulse Current (5 Sec.)	Cold Cranking Amps (CCA)	Reserve Capacity Minutes	Length inches (mm)	Width inches (mm)	Height inches (mm) Terminal Included	Weight lbs (kg)
34M-PC1500 	12	1500	850	135	10.86 (275.8)	6.77 (172.0)	7.95 (201.9)	49.5 (22.4)
31M-PC2150 	12	2150	1150	205	13.00 (330.2)	6.80 (172.7)	9.39 (238.5)	77.8 (35.3)
PC2250 	12	2250	1225	240	11.26 (286.0)	10.59 (269.0)	9.17 (233.0)	86.0 (39.0)



<b>Capacity Range</b>	68-100 Ah
<b>Construction</b>	Thin Plate Pure Lead (TPPL) Absorbent Glass Mat (AGM)
<b>Case Material</b>	Polycarbonate Blend*
<b>Terminals</b>	Tin-Coated Brass**
<b>Top Lead Style</b>	Over-the-wall***
<b>Warranty</b>	Limited 4-year replacement period; 2-year in APU applications

\*Polycarbonate Blend - Stronger for more rugged environment

\*\*Tin-Coated Brass - Provides higher conductivity for higher capacity, as compared to solid lead

\*\*\*Over-the-wall - Offers lower resistance for higher capacity, as compared to through-the-wall type

## ODYSSEY® Performance Series™ battery

Battery Type	Voltage	Pulse Current (5 Sec.)	Cold Cranking Amps (CCA)	Reserve Capacity Minutes	Length inches (mm)	Width inches (mm)	Height inches (mm) Terminal Included	Weight lbs (kg)
34M-790 	12	1500	792	124	10.85 (275.6)	6.78 (172.2)	7.91 (200.9)	47.6 (21.5)
31-925 	12	1750	925	200	13.0 (330.2)	6.78 (172.2)	9.60 (243.8)	70.1 (31.8)
4D-1300 	12	2400	1300	370	20.39 (518.0)	8.78 (223.0)	8.58 (218.0)	117.3 (53.3)
8D-1500 	12	2700	1500	475	20.39 (518.0)	10.87 (276.0)	8.86 (225.0)	143.0 (65.0)

<b>Capacity Range</b>	61-220 Ah
<b>Construction</b>	Thin Plate Pure Lead (TPPL) Absorbent Glass Mat (AGM)
<b>Case Material</b>	Polypropylene
<b>Terminals</b>	Solid Lead
<b>Top Lead Style</b>	Through-the-wall
<b>Warranty</b>	Limited 3-year replacement period; 2-year in APU applications



**EnerSys World Headquarters**  
2366 Bernville Road  
Reading, PA 19605, USA  
Tel: +1-610-208-1991 /  
+1-800-538-3627

**EnerSys EMEA**  
EH Europe GmbH  
Baarerstrasse 18  
6300 Zug, Switzerland

**EnerSys Asia**  
152 Beach Road  
#11-08 Gateway East Building  
Singapore 189721  
Tel: +65 6416 4800

Want more info?  
Scan code to access  
the ODYSSEY® Battery  
Literature Library

