## POWER TO GO WHEREVER THE ROAD TAKES YOU

# Get out there and stay out there

Traditionally, selecting an RV battery meant choosing between a starting battery with enough cranking amps to start the vehicle's engine, or a deep cycle battery with enough reserve power to run the vehicle's accessories. With an ODYSSEY® battery, those days are in the rearview. ODYSSEY batteries pack big starting power and deep cycle reserve power in a robust design that's built for the longest hauls.

ODYSSEY Performance batteries deliver more overall power and longer service life than conventional batteries, while ODYSSEY Extreme batteries deliver twice the overall power and three times the life of conventional batteries.



### **MILITARY GRADE PLATE DESIGN**

Made from 99% pure lead and built to stand up to the harshest environments. ODYSSEY batteries offer slower self-discharge, less corrosion and faster recharging.

### **VIBRATION RESISTANCE**

Protection against high impact shock and vibration that cause premature battery failure.

### **EXTREME TEMPERATURE TOLERANCE**

Operating temperatures: -40°F (-40°C) to 140°F (60°C) – Performance batteries -40°F (-40°C) to 176°F (80°C) – Extreme batteries

### LONGER SERVICE LIFE

Three times longer than conventional batteries.



www.odysseybattery.com



# **ODYSSEY® Extreme Batteries**

PART NUMBER	PHCA 5 sec [A]	MCA [A]	Ah at 20-hr rate	Reserve Capacity [Minutes]	Maximum Length [in (mm)]	Maximum Width [in (mm)]	Maximum Total Height [in (mm)]	Maximum Container Height [in (mm)]	Weight [lb (kg)]
ODX-AGM24M	1500	1010	76	160	10.9 (276)	6.8 (172)	8.8 (222)	8.1 (206)	57 (26.0)
ODX-AGM34M	1500	1050	68	135	10.9 (276)	6.8 (172)	8.0 (202)	7.3 (184)	50 (22.5)
ODX-AGM27M	1750	1080	92	195	12.4 (315)	6.8 (172)	8.8 (222)	8.1 (206)	68 (31.0)
ODX-AGM65M	1750	1070	69	135	11.8 (299)	7.3 (186)	7.4 (188)	6.8 (172)	54 (24.5)
ODX-AGM31M	2150	1370	100	220	13.0 (331)	6.8 (173)	9.4 (239)	8.6 (218)	78 (35.5)
ODS-AGM6M	2250	1550	114	240	11.3 (286)	10.6 (269)	9.2 (233)	9.2 (233)	86 (39.0)
ODX-AGM8DK	3125	2700	228	500	21.0 (521)	11 (279)	9.4 (239)	8.0 (206)	187 (85.0)
ODX-AGM8DKDT	3125	2700	228	500	21.0 (521)	11 (279)	9.4 (239)	8.0 (206)	187 (85.0)
ODX-AGM8DKT	3125	2700	228	500	21.0 (521)	11 (279)	9.4 (239)	8.0 (206)	187 (85.0)

Construction	Thin Plate Pure Lead (TPPL) Absorbed Glass Mat (AGM)						
Case Material	Polycarbonate Blend*						
Terminals	Tin-Coated Brass/Solid Brass**						
Top Lead Style	Over-the-wall***						
Warranty	Limited 4-year replacement period on starting; limited 2-year on back-up						

# **ODYSSEY®** Performance Batteries

PART NUMBER	PHCA 5 sec [A]	MCA [A]	Ah at 20-hr rate	Reserve Capacity [Minutes]	Maximum Length [in (mm)]	Maximum Width [in (mm)]	Maximum Total Height [in (mm)]	Maximum Container Height [in (mm)]	Weight [Ib (kg)]
ODP-AGM24M	1300	825	63	155	10.9 (276)	6.8 (172)	8.9 (225)	8.1 (206)	51 (23.0)
ODP-AGM27M	1500	975	85	182	12.4 (316)	5.8 (147)	8.9 (225)	8.1 (206)	60 (27.0)
ODP-AGM34M	1300	810	60	120	10.8 (275)	6.8 (172)	7.9 (201)	7.4 (187)	48 (21.5)
ODP-AGM31M	1750	1050	87	190	13.0 (330)	6.8 (173)	9.5 (240)	8.6 (220)	69 (31.5)
ODP-AGM4D	2400	1549	170	370	20.4 (518)	8.8 (223)	8.6 (218)	8.3 (208)	117 (53.5)
ODP-AGM8D	2700	1787	220	475	20.4 (518)	10.9 (276)	8.9 (225)	8.5 (215)	143 (65.0)

Construction	Thin Plate Pure Lead (TPPL) Absorbed Glass Mat (AGM)						
Case Material	Polypropylene						
Terminals	Solid Lead/Solid Brass**						
Top Lead Style	Through-the-wall						
Warranty	Limited 3-year replacement period on starting; limited 2-year on back-up						

\*Polycarbonate Blend – Stronger for more rugged environments \*\*Brass – Provides higher conductivity for higher capacity, as compared to solid lead \*\*\*Over-the-wall – Offers lower resistance for higher capacity, as compared to through-the-wall type



**EnerSys World Headquarters** 2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837

EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland

EnerSys Asia 152 Beach Road #11-08 Gateway East Building Singapore 189721 Tel: +65 6431 3700

© 2022 EnerSys. All rights reserved. Trademarks and logos are the property of EnerSys and its affiliates unless otherwise noted. Subject to revisions without prior notice. E.&O.E. AMER-EN-FLY-ODY-RV-1222

Want more info? Scan code to access the ODYSSEY® Battery Literature Library



12 volt

12 volt